



REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
C	ECN-11-1633		依客户要求去掉机身后面两条筋	2012.02.15	卢桂斌
D	ECN-11-1652	(D) x1	依客户要求将A部分开, 新增引脚, 取消PJ-0268500-065-182 镀金15μ"规格	2012.03.27	李小姐
E	ECN-11-1675		取消PJ-0268500-061-182镀金1u"规格	2012.06.04	卢桂斌

TABLE A:

MATTER	RoHS (PPM)
Cd	≤ 100
Pb	≤ 1000
Hg	≤ 1000
Cr+6	≤ 1000
PBB	≤ 1000
PBDE	≤ 1000



品赞电子 尽善尽美






TABLE B:

ITEM	PART NUMBER	DESCRIPTION
TYPE 1	PJ-0268500-062-182	WITH LOGO
TYPE 2	PJ-026850P-062-182	NO LOGO

- NOTES:
- CONTACT CURRENT RATING: 1A;
 - CONTACT RESISTANCE: 50mΩ MAX.;
 - INSULATION RESISTANCE: 100MΩ MIN.;
 - DIELECTRIC WITHSTANDING: 500V AC MIN.;
 - DURABILITY: 10,000CYCLES.;
 - CONNECTOR MATING FORCES: 2.94~29.4N (0.30~3.00kgf).;
 - CONNECTOR UNMATING FORCES: 2.94~29.4N (0.30~3.00kgf).;
 - PRODUCT MEET THE REQUEST OF THE RoHS, SEE TABLE A;



01	HOUSING	1 PCS	HIGHT TEMPERATURE PLASTIC	BLACK COLOR	UL94V-0
02	CONTACT A	1 PCS	PHOSPHOR BRONZE 0.20T	Contact:2u" Au/Other:1u"Au	
03	CONTACT B	1 PCS	PHOSPHOR BRONZE 0.20T	Contact:2u" Au/Other:1u"Au	
04	CONTACT C	1 PCS	PHOSPHOR BRONZE 0.20T	Contact:2u" Au/Other:1u"Au	
05	CONTACT D	1 PCS	STAINLESS STEEL 0.20T	Contact:2u" Au/Other:1u"Au	
06	CONTACT E	1 PCS	STAINLESS STEEL 0.20T	Contact:2u" Au/Other:1u"Au	
07	CONTACT F	1 PCS	BRASS 0.20T	1u"Au All Over	(D)
ITEM	PART NAME	Q'TY	MATERIAL	DESCRIPTION	REMARK

<p>Unless otherwise specified, Tolerance: % ±0.30 X.X ±0.20 X.XX ±0.15 X.XXX ±0.10 Angles ±3°</p>	G-Switch Electronic Technology CO.,Ltd.	
	DESIGN 卢桂斌	DATE: 2012.06.04
	CHECKED	DATE
	APPROVED	DATE
PART NO.SEE TABLE B	REV: E	SCALE: 1:1
DRAWING NO.C-PJ0268500-00	SIZE: A4	SHEET: 1/1