

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A	N/A		INITIAL RELEASE	2012.04.28	李小珍





TABLE A:

MATTER	RoHS ( PPM )
Cd	≤ 100
Pb	≤ 1000
Hg	≤ 1000
Cr6+	≤ 1000
PBB	≤ 1000
PBDE	≤ 1000





TABLE B:

ITEM	PART NUMBER	DESCRIPTION
TYPE 1	PJ-0272DOP-062-1B2	WITH LOGO; 不喷码; 不粘高温胶纸
TYPE 2	PJ-0272DOP-062-1B5	WITH LOGO; 不喷码; 粘高温胶纸
TYPE 3	PJ-0272DOP-062-1B2	WITH LOGO; 不喷码; 不粘高温胶纸
TYPE 4	PJ-0272DOP-062-1B6	WITH LOGO; 喷码; 不粘高温胶纸
TYPE 5	PJ-0272DOP-062-1B2	NO LOGO; 不喷码; 不粘高温胶纸



- NOTES:
- CONTACT CURRENT RATING: 1A.
  - CONTACT RESISTANCE: 50mΩ MAX.
  - INSULATION RESISTANCE: 100MΩ MIN.
  - DIELECTRIC WITHSTANDING: 500V AC MIN.
  - DURABILITY: 10,000CYCLES;
  - CONNECTOR MATING FORCES: 2.94~29.4N (0.30~3.00kgf);
  - CONNECTOR UNMATING FORCES: 2.94~29.4N (0.30~3.00kgf);
  - PRODUCT MEET THE REQUEST OF THE RoHS, SEE TABLE A;



01	HOUSING	1 PCS	HIGHT TEMPERATURE PLASTIC	BLACK COLOR	UL94V-0
02	CONTACT A	1 PCS	PHOSPHOR BRONZE 0.20T	CONTACT:2u"Au;OTHER:1u" Au	
03	CONTACT B	1 PCS	PHOSPHOR BRONZE 0.20T	CONTACT:2u"Au;OTHER:1u" Au	
04	CONTACT C	1 PCS	PHOSPHOR BRONZE 0.20T	CONTACT:2u"Au;OTHER:1u" Au	
05	CONTACT D	1 PCS	STAINLESS STEEL 0.20T	CONTACT:2u"Au;OTHER:1u" Au	
06	CONTACT E	1 PCS	STAINLESS STEEL 0.20T	CONTACT:2u"Au;OTHER:1u" Au	
07	MYLAR	1 PCS	PET 0.08T	YELLOW COLOR	
ITEM	PART NAME	Q'TY	MATERIAL	DESCRIPTION	REMARK

<p>Unless otherwise specified, Tolerance:  X: ±0.30  X.X: ±0.20  X.XX: ±0.15  X.XXX: ±0.10  Angles: ±3°</p>	<b>G-Switch Electronic Technology CO., Ltd.</b>	
	DESIGN	李小珍 DATE: 2012.04.28
	CHECKED	DATE
	APPROVED	DATE
PART NO.SEE TABLE B,C	REV: A SCALE: 1:1	TITLE: Ø3.5 4 POLE PHONE JACK CUSTOMER DRAWING
DRAWING NO.C-PJ0272DOP-0D	SIZE: A4 SHEET: 1/1	UNIT: mm