

GT-USB-2110-XXGX

G-Switch

USB系列

系列编码

C=铜壳
S=不锈钢

G1=1U
G3=3U
G5=5U
G15=15U
G30=30U

B=黑色

N=其它



Note:

1.Material:

- 1.1 Housing: LCP High temperature thermoplastic with g.f.I/L94v-0
- 1.2 Contact: copper alloy,t=0.15mm
- 1.3 Shell: SUS304,t=0.30mm


2.Specification:

- 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 100 MΩ Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.
- 2.7 Temperature range: -30°C~80°C



RECOMMENDED PCB LAYOUT(TOP VIEW)

GENERAL TOLERANCES:±0.05



RoHS
Compliant
2002/95/EC



G-Switch Electronic Technology CO., Ltd.

Unless otherwise specified, Tolerance:
X ±0.30
X.x ±0.20
X.xx ±0.15
X.xxx ±0.10
Angles ±3°

| | | |
|---|-----------------|-----------------------------|
| DESIGN 原研机 | DATE 2016.05.29 | TITLE: |
| CHECKED | DATE | GT-USB-2110-XXGX |
| APPROVED | DATE | |
| http://www.dg-switch.com | | REV: X1 SCALE: 4:1 UNIT: mm |
| TEL:0769-82388879 | | SIZE: A4 SHEET: 1/1 |

REV: X1 SCALE: 4:1 UNIT: mm

SIZE: A4 SHEET: 1/1