


2-5Pin



6-15Pin



GT-A2508 C 1 -1 XX X 01

**G-Switch**  
**Series No**  
**Connector**  
 C-Cover  
**1-Type 1**

**Housing Colour**  
 B-Black  
**Pin Q' PY**  
 02~15  
**Row NO**  
 1-Single Row

**G-Switch Specification:**

- 1.Current rated: 3.0A AC/DC
- 2.Voltage rating: 250V AC/DC
- 3.Withstanding voltage: 1000V AC
- 4.Contact resistance: 10mΩ max.
- 5.Insulation resistance: 1000MΩ min
- 6.Durability cycle: 50Cycles
- 7.Removal force: 2.0kgf/Pin min
- 8.Operating temperature range: -25°C ~ +85°C

**Ordering Information:**

Circuit	Dimensions(mm)			Circuit	Dimensions(mm)		
	A	B	C		A	B	C
02	---	---	3.80	09	20.00	15.00	21.30
03	5.00	---	6.30	10	22.50	17.50	23.80
04	7.50	---	8.80	11	25.00	20.00	26.30
05	10.00	---	11.30	12	27.50	22.50	28.80
06	12.50	7.50	13.80	13	30.00	25.00	31.30
07	15.00	10.00	16.30	14	32.50	27.50	33.80
08	17.50	12.50	18.80	15	35.00	30.00	36.30

1	COVER	PA66,94V-0	BLACK
NO.	PART NAME	MATERIAL	REMARK



SCALE: 1:1 UNIT: mm  
 SIZE: A4

Unless otherwise General Tolerance:  
 X ±0.40  
 X.x ±0.30  
 X.xx ±0.20  
 X° ±5°  
 X.x° ±3°

Title: Cover 2.50mm Pitch XA Single Row  
 Molde Code: GT-A2508C1-1XXX01

DRAWN	CHECKED	APPROVED	DATE
Hu	Hu	Chen	2021.10.20



REV: A0 SHEET: 1/1