









SECCION:A-A



G-Switch Specification:

- 1.Current rated: 0.8~2.5A AC/DC
- 2.Voltage rating: 100V AC/DC
- 3.Withstanding voltage: 300V AC
- 4.Contact resistance: 20mΩ max.
- 5.Insulation resistance: 100MΩ min
- 6.Durability cycle: 50Cycles
- 7.Removal force: 1.0kgf/Pin min
- 8.Operating temperature range: -40°C ~ +85°C



GT-A0801 H M -1 XX X 01

G-Switch

Series No-

Connector

H-Housing

M-Male

Housing Colour
B-Black

Pin Q' PY
02~20

Row NO
1-Single Row

Ordering Information:

Circuit	Dimensions(mm)		Circuit	Dimensions(mm)	
	A	B		A	B
02	---	3.50	12	8.80	11.50
03	1.60	4.30	13	9.60	12.30
04	2.40	5.10	14	10.40	13.10
05	3.20	5.90	15	11.20	13.90
06	4.00	6.70	16	12.00	14.70
07	4.80	7.50	17	12.80	15.50
08	5.60	8.30	18	13.60	16.30
09	6.40	9.10	19	14.40	17.10
10	7.20	9.90	20	15.20	17.90
11	8.00	10.70	---	---	---

SCALE: 1:1	UNIT: mm	Title: Housing 0.80mm Pitch HRS Single Row Male				 品赞科技 ® -Switch www.dg-switch.com	
SIZE: A4							
Unless otherwise General Tolerance: X ±0.40 X.x ±0.30 X.xx ±0.20 X° ±5° X.x° ±3°		Molde Code: GT-A0801HM-1XXX01					
		DRAWN	CHECKED	APPROVED	DATE		
		Hu	Hu	Chen	2021.10.20	REV: A0	SHEET: 1/1