







RECOMMENDED PCB LAYOUT
TOLERANCE:±0.05



GT-TCB60X-HXXX-LX

Operating Force

A=160gf
B=250gf
C=100gf

Switch Height(mm)

H025=2.50
H027=2.70


Switch Lifetime (Force)

L05=50,000 Cycles
L1=100,000 Cycles

G-Switch Specification:

1. Operating temperature range: -40°C ~ +85°C
2. Rating: 50mA, 12V DC
3. Insulation resistance: 100MQ min, 100V DC
4. Dielectric strength: 250V AC for 1 min
5. Contact resistance: 100m Ω max.
6. Travel: 0.25±0.1mm

6	COVER	STAINLESS STEEL	-
5	STEM	LCP	RED
4	TAPE	PI	YELLOW (TRANSPARENT)
3	CONTACT	STAINLESS STEEL	Ag PLATING
2	TERMINAL	COPPER ALLOY	Ag PLATING
1	BASE	HIGH TEMPERATURE PLASTIC	LCP BLACK
NO.	PART NAME	MATERIAL	REMARK



CIRCUIT DIAGRAM



SCALE: 1:1 UNIT: mm
SIZE: A4

Unless otherwise
General Tolerance:

X. ±0.40
X.x ±0.30
X.xx ±0.20
X° ±3°

Title: Vertical Tact Switch
U Type 6.1×3.7×Hmm

Molde Code: GT-TCB60X-HXXX-LX

DRAWN	CHECKED	APPROVED	DATE
Jiang	Xia	Chen	2025.02.25



REV: A0 SHEET: 1/1