












SECTION A-A



AFTER MATING

**G-Switch USB-C Specification:**

1. Current rated: 5A on vbus/1.25A on vconn/0.25A on other
2. Voltage rating: 24V AC
3. Withstanding voltage: 100V AC/minute
4. Contact resistance: 40mΩ Max
5. Insulation resistance: 100MΩ Min
6. Operating temperature: -40°C ~ +85°C
7. Mating force: 5N~20N
8. Unmating force: 8N~20N
9. Durability cycle: 10,000 cycles
9. Compliant with: IEC62680-1-3

RECOMMENDED PCB LAYOUT
TOLERANCE:±0.05

SECTION B-B

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND			VBUS	CC1	D+	D-	SBU1	VBUS			GND
First			First	Second	Second	Second	Second	First			First

B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND			VBUS	SBU2	D-	D+	CC2	VBUS			GND
First			First	Second	Second	Second	Second	First			First

NO.	PARTS	MATERIAL	REMARKS
1	COVER SHELL	STAINLESS STEEL304	Ni30u"MIN PLATED
2	INNER SHELL	STAINLESS STEEL304	Ni30u"MIN PLATED
3	MID PLATE	STAINLESS STEEL301	—
4	HOUSING	HIGH TEMPERATURE PLASTIC	LCP BLACK UL 94 V-0
5	TERMINALS	COPPER ALLOY C7025	Au1u"MIN PLATING ON CONTACT AREA Tin30u"MIN PLATING ON SOLDER AREA



SCALE: 1:1 UNIT: mm
SIZE: A4

Unless otherwise
General Tolerance:
X. ±0.40
X.x ±0.30
X.xx ±0.20
X.xxx ±0.10
X" ±5°

Title: Horizontal Type-c 16P Female SMT
Pad Up5.37 CH=6.95 L=7.4mm

Molde Code: GT-USB-9016G

DRAWN	CHECKED	APPROVED	DATE
Xia	Chen	Chen	2024.03.10

品赞科技
b-Switch
www.dg-switch.com

REV: A0 SHEET: 1/1