





- 1.Current rated: 3.0A AC/DC
- 2.Voltage rating: 250V AC/DC
- 3.Withstanding voltage: 1500V AC
- 4.Contact resistance: 20mΩ max.
- 5.Insulation resistance: 1000MΩ min
- 6.Durability cycle: 50Cycles
- 7.Removal force: 1.50kgf/Pin min
- 8.Operating temperature range: -25°C ~ +85°C



— **Row NO**
1-Single row



A schematic diagram of a rectangular room. The room has a central area and three small square features arranged horizontally in the center. The room is enclosed by a thick border, and there are small semi-circular shapes at the top and bottom center, possibly representing doors or windows.

2Pin

Circuit	Dimensions(mm)			Circuit	Dimensions(mm)		
	A	B	C		A	B	C
02	--	5.56	7.62	12	27.94	30.96	33.02
03	5.08	8.10	10.16	13	30.48	33.50	35.56
04	7.62	10.64	12.70	14	33.02	36.04	38.10
05	10.16	13.18	15.24	15	35.56	38.58	40.64
06	12.70	15.72	17.78	16	38.10	41.12	43.18
07	15.24	18.26	20.32	17	40.64	43.66	45.72
08	17.78	20.80	22.86	18	43.18	46.20	48.26
09	20.32	23.34	25.40	19	45.72	48.74	50.80
10	22.86	25.88	27.94	20	48.26	51.28	53.34
11	25.40	28.42	30.48	--	--	--	--

 品赞科技
www.dq-switch.com

REV: A0	SHEET: 1/1
---------	------------

2	PIN MATERIAL	BRASS	ALL G/F
1	HOUSING	PA66+15%GF,94V-0	BLACK
NO.	PART NAME	MATERIAL	REMARK

