


G-Switch USB-C Specification:

1. Current rated: 5A on vbus/1.25A on vconn/0.25A on other
2. Voltage rating: 24V AC
3. Withstanding voltage: 100V AC/minute
4. Contact resistance: 40mΩ Max
5. Insulation resistance: 100MΩ Min
6. Operating temperature: -40°C ~ +85°C
7. Mating force: 5N~20N
8. Unmating force: 8N~20N
9. Durability cycle: 10,000 cycles
9. Data transmission rate up to 5Gbps

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	VBUS	CC1	D+	D-	SBU1	VBUS	RX2-	RX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1
GND	RX1+	RX1-	VBUS	SBU2	D-	D+	CC2	VBUS	TX2-	TX2+	GND
First	Second	Second	First	Second	Second	Second	Second	First	Second	Second	First

1	COVER SHELL	STAINLESS STEEL304	Ni PLATED
2	SHELL	STAINLESS STEEL304	Ni PLATED
3	GND PLATE	STAINLESS STEEL304	---
4	MID PLATE	STAINLESS STEEL301	Ni PLATED
5	HOUSING	HIGH TEMPERATURE PLASTIC	LCP BLACK UL 94 V-0
6	TERMINALS	COPPER ALLOY C7025	Au PLATING ON CONTACT AREA G/F PLATING ON CONTACT AREA
NO.	PARTS	MATERIAL	REMARKS

PCB REFERENCE DIAGRAM
TOLERANCE:±0.05



SCALE: 1:1 UNIT: mm
SIZE: A4

Unless otherwise
General Tolerance:
X. ±0.40
X.x ±0.30
X.xx ±0.20
X.xxx ±0.10
X* ±5°

Title: Horizontal Type-c 24P Female
SMT Sink0.94 CH=0.64 L=12.85mm

Molde Code: GT-USB-7068B

DRAWN	CHECKED	APPROVED	DATE
Xia	Chen	Chen	2024.11.15



REV: A0 SHEET: 1/1