

GT-A2012 H M -2 XX X 01

G-Switch
Series No
Connector
 H-Housing
M-Male

Housing Colour
 W-White

Pin Q' PY
 08~40

Row NO
 2-Dual Rows

- G-Switch Specification:**
- 1.Current rated: 3.0A AC/DC
 - 2.Voltage rating: 250V AC/DC
 - 3.Withstanding voltage: 800V AC
 - 4.Contact resistance: 10mΩ max.
 - 5.Insulation resistance: 1000MΩ min
 - 6.Durability cycle: 30Cycles
 - 7.Removal force: 1.00kgf/Pin min
 - 8.Operating temperature range: -25°C ~ +85°C

Ordering Information:

Circuit	Dimensions(mm)			Circuit	Dimensions(mm)		
	A	B	C		A	B	C
08	6.00	10.00	8.65	26	24.00	28.00	26.65
10	8.00	12.00	10.65	28	26.00	30.00	28.65
12	10.00	14.00	12.65	30	28.00	32.00	30.65
14	12.00	16.00	14.65	32	30.00	34.00	32.65
16	14.00	18.00	16.65	34	32.00	36.00	34.65
18	16.00	20.00	18.65	36	34.00	38.00	36.65
20	18.00	22.00	20.65	38	36.00	40.00	38.65
22	20.00	24.00	22.65	40	38.00	42.00	40.65
24	22.00	26.00	24.65	--	--	--	--

1	HOUSING	PA66,94V-0	WHITE
NO.	PART NAME	MATERIAL	REMARK



SCALE: 1:1 UNIT: mm
 SIZE: A4

Unless otherwise General Tolerance:
 X ±0.40
 X.x ±0.30
 X.xx ±0.20
 X° ±5°
 X.x° ±3°

Title: Housing 2.00mm Pitch PUD Dual Rows Male

Molde Code: GT-A2012HM-2XXX01

DRAWN	CHECKED	APPROVED	DATE
Hu	Hu	Chen	2021.10.20



REV: A0 SHEET: 1/3

1

2



3

4

5

A

A



8Pin

10Pin

12Pin

14Pin

16Pin



18Pin

B

B

C

C



20Pin

22Pin

24Pin

26Pin

D

D

E

E



GT-A2012 H M -2 XX X 01

G-Switch

Series No

Connector
H-Housing

M-Male

Housing Colour
W-White

Pin Q' PY
08-40

Row NO
2-Dual Rows

G-Switch Specification:

- 1.Current rated: 3.0A AC/DC
- 2.Voltage rating: 250V AC/DC
- 3.Withstanding voltage: 800V AC
- 4.Contact resistance: 10mΩ max.
- 5.Insulation resistance: 1000MΩ min
- 6.Durability cycle: 30Cycles
- 7.Removal force: 1.00kgf/Pin min
- 8.Operating temperature range: -25°C ~ +85°C

SCALE: 1:1 UNIT: mm

SIZE: A4

Title: Housing 2.00mm Pitch PUD Dual Rows Male

Molde Code: GT-A2012HM-2XXX01

Unless otherwise
General Tolerance:

X	±0.40
X.x	±0.30
X.xx	±0.20
X*	±5°
X.x°	±3°

DRAWN	CHECKED	APPROVED	DATE
Hu	Hu	Chen	2021.10.20



REV: A0 SHEET: 2/3

1	HOUSING	PA66,94V-0	WHITE
NO.	PART NAME	MATERIAL	REMARK



1

2

3

4

5

1

2


3

4

5


A

A



B

B



GT-A2012 H M -2 XX X 01

G-Switch

Series No

Connector
H-Housing

M-Male

Housing Colour
W-White

Pin Q' PY
08-40

Row NO
2-Dual Rows

28Pin


30Pin

32Pin

34Pin


C

C



D

D



36Pin

38Pin

40Pin

G-Switch Specification:

- 1.Current rated: 3.0A AC/DC
- 2.Voltage rating: 250V AC/DC
- 3.Withstanding voltage: 800V AC
- 4.Contact resistance: 10mΩ max.
- 5.Insulation resistance: 1000MΩ min
- 6.Durability cycle: 30Cycles
- 7.Removal force: 1.00kgf/Pin min
- 8.Operating temperature range: -25°C ~ +85°C

SCALE: 1:1 UNIT: mm
 SIZE: A4

Title: Housing 2.00mm Pitch PUD Dual Rows Male

Unless otherwise
General Tolerance:

X ±0.40
 X.x ±0.30
 X.xx ±0.20
 X* ±5°
 X.x° ±3°

Molde Code: GT-A2012HM-2XXX01

DRAWN	CHECKED	APPROVED	DATE
Hu	Hu	Chen	2021.10.20



REV: A0 SHEET: 3/3



HOUSING	PA66,94V-0	WHITE
PART NAME	MATERIAL	REMARK

1

2

3

4

5

E

E