


GT-B0502 M S V 27 -XX X XX 02


Angle
V-180°

— **Height**
27-2.75mm



- 1.Current rated: 0.3A AC/DC
- 2.Voltage rating: 50V AC/DC
- 3.Withstanding voltage: 150V AC
- 4.Contact resistance: 50mΩ Max.
- 5.Insulation resistance: 500MΩ min
- 6.Durability cycle: 30 Cycles
- 7.Removal force: 0.30kgf/Pin min
- 8.Operating temperature range: -40°C ~ +85°C

Circuit	Dimensions(mm)				Circuit	Dimensions(mm)			
	A	B	C	D		A	B	C	D
10	4.70	2.00	3.10	4.10	32	10.20	7.50	8.60	9.60
12	5.20	2.50	3.60	4.60	36	11.20	8.50	9.60	10.60
14	5.70	3.00	4.10	5.10	40	12.20	9.50	10.60	11.60
20	7.20	4.50	5.60	6.60	50	14.70	12.00	13.10	14.10
22	7.70	5.00	6.10	7.10	60	17.20	14.50	15.60	16.60
24	8.20	5.50	6.60	7.60	70	19.70	17.00	18.10	19.10
30	9.70	7.00	8.10	9.10	80	22.20	19.50	20.60	21.60



SCALE: 1:1	UNIT: mm
SIZE: A4	

Title: BTB 0.50mm Pitch 180° H2.7mm Dual Rows
SMT Type Mate Connector

Molde Code: GT-B0502MSV27-XXXXX02

DRAWN	CHECKED	APPROVED	DATE
Hu	Chen	Chen	2022.12.28

 品赞科技
b-Switch
www.dg-switch.com

Unless otherwise	
General Tolerance:	
X	±0.40
X.x	±0.30
X.xx	±0.20
X°	±5°
X.x°	±3°

REV: A0	SHEET: 1/1
---------	------------