



E

| Circuit | Dimensions(mm) |       |       |       | Circuit | Dimensions(mm) |       |       |       |
|---------|----------------|-------|-------|-------|---------|----------------|-------|-------|-------|
|         | A              | B     | C     | D     |         | A              | B     | C     | D     |
| 10      | 3.20           | 4.90  | 11.30 | 8.20  | 50      | 19.20          | 20.90 | 27.30 | 24.20 |
| 12      | 4.00           | 5.70  | 12.10 | 9.00  | 60      | 23.20          | 24.90 | 31.30 | 28.20 |
| 16      | 5.60           | 7.30  | 13.70 | 10.60 | 70      | 27.20          | 28.90 | 35.30 | 32.20 |
| 20      | 7.20           | 8.90  | 15.30 | 12.20 | 80      | 31.20          | 32.90 | 39.30 | 36.20 |
| 24      | 8.80           | 10.50 | 16.90 | 13.80 | 100     | 39.20          | 40.90 | 47.30 | 44.20 |
| 30      | 11.20          | 12.90 | 19.30 | 16.20 | 120     | 47.20          | 48.90 | 55.30 | 52.20 |
| 40      | 15.20          | 16.90 | 23.30 | 20.20 | 140     | 55.20          | 56.90 | 63.30 | 60.20 |



- 1.Current rated: 0.5A AC/DC
2. Voltage rating:100V AC/DC
- 3.Withstanding voltage: 500V AC
- 4.Contact resistance: 60mΩ Max.
- 5.Insulation resistance: 500MΩ min
- 6.Durability cycle: 50 Cycles
- 7.Removal force: 0.01kgf/Pin min
- 8.Operating temperature range: -40°C ~ +85°C



B

— **Height(H1)**  
40-4.00mm  
90-9.00mm

D

|         |            |
|---------|------------|
| REV: A0 | SHEET: 1/1 |
|---------|------------|

