



GT-A1259 H M -2 XX X 01


G-Switch
Series No
Connector
H-Housing
M-Male
Housing Colour
W-White
B-Black
Pin Q' PY
10~40
Row NO
2-Dual Rows



G-Switch Specification:
1.Current rated: 1.0A AC/DC
2.Voltage rating: 50V AC/DC
3.Withstanding voltage: 500V AC
4.Contact resistance: 50mΩ max.
5.Insulation resistance: 100MΩ min
6.Durability cycle: 30Cycles
7.Removal force: 0.30kgf/Pin min
8.Operating temperature range: -25°C ~ +85°C

Ordering Information:

Circuit	Dimensions(mm)		Circuit	Dimensions(mm)	
	A	B		A	B
10	9.50	5.00	26	19.50	15.00
12	10.75	6.25	28	20.75	16.25
14	12.00	7.50	30	22.00	17.50
16	13.25	8.75	32	23.25	18.75
18	14.50	10.00	34	24.50	20.00
20	15.75	11.25	36	25.75	21.25
22	17.00	12.50	38	27.00	22.50
24	18.25	13.75	40	28.25	23.75



1	HOUSING	PA66,94V-0	WHITE/BLACK
NO.	PART NAME	MATERIAL	REMARK



SCALE: 1:1	UNIT: mm	Title: Housing 1.25mm Pitch GHD Dual Rows Male			
SIZE: A4		Molde Code: GT-A1259HM-2XXX01			
Unless otherwise General Tolerance: X ±0.40 X.x ±0.30 X.xx ±0.20 X° ±5° X.x° ±3°		DRAWN	CHECKED	APPROVED	DATE
		Hu	Hu	Chen	2021.10.20



REV: A0	SHEET: 1/1
---------	------------